



Solderless Lugs

TYPE: CF/CFS



90°C RATING (486B LISTED)

CMC[®] Single hole solderless lugs are manufactured from high strength pure electrolytic copper to insure both maximum strength and conductivity. Conductors are inserted between arched pressure bar and V- bottom collar which positions the wire for positive contact and maximum secureness. Easy to install with screwdriver, wrench or pliers and reuseable. Plain copper finish.



Catalog Number	Fig. No.	Cond. Range AWG	Mtg Hole	Dimensions, Inches		
				H	W	L
CF-25	1	10 - 14	0.16	0.66	0.31	1
CF-35	1	6 - 14	0.2	0.75	0.38	1.19
CF-70	1	4 - 14	0.27	0.81	0.5	1.31
CF-90	1	2 - 8	0.27	1	0.5	1.22
CF-125	2	1/0 - 2	0.27	1.34	0.63	1.97
CF-175	2	3/0 - 4	0.41	1.56	0.75	2.19
CF-225	2	4/0 - 2	0.41	1.81	1	2.63
CF-300	2	350 - 1/0	0.41	2.63	1	3.19
CF-400	2	500 - 1/0	0.41	2.75	1.5	4.25
CF-650	2	1000 - 600	0.53	3.69	2	4.63
CFS-25	3	10 - 14	0.16	0.66	0.31	0.95
CFS-35	3	6 - 14	0.2	0.75	0.38	1.19
CFS-70	3	4 - 14	0.27	0.81	0.5	1.31
CFS-90	3	2 - 8	0.27	1	0	1.22
CFS-125	3	1/0 - 2	0.41	1.34	0	1.97
CFS-175	4	3/0 - 4	0.41	1.56	0.75	2.19
CFS-225	4	4/0 - 2	0.41	1.81	0	2.63
CFS-300	4	350 - 1/0	0.41	2.63	0	3.19
CFS-400	4	500 - 1/0	0.41	2.75	0	4.25
CFS-650	4	1000 - 600	0.53	3.69	0	4.63

