
	<h2>Pan Head</h2>	
Slotted	Commonly used with Machine Screws, Self-Tapping, Self-Drilling, Thread Forming screws.	Phillips

Nominal Size	A		H		H1		J		T		M		G	N	Phillips Driver Size
	Head Diameter		Height of Head				Width of Slot		Depth of Slot		Dimensions of Recess				
	Max.	Min.	Slotted		Recessed		Max.	Min.	Max.	Min.	Diameter	Depth	Width		
2	.167	.155	.053	.045	.062	.053	.031	.023	.031	.022	.104	.091	.059	.017	1
3	.193	.180	.060	.051	.071	.062	.035	.027	.036	.026	.112	.099	.068	.019	1
4	.219	.205	.068	.058	.080	.070	.039	.031	.040	.030	.122	.109	.078	.019	1
5	.245	.231	.075	.065	.089	.079	.043	.035	.045	.034	.158	.145	.083	.028	2
6	.270	.256	.082	.072	.097	.087	.048	.039	.050	.037	.166	.153	.091	.028	2
7	.296	.281	.089	.079	.106	.096	.048	.039	.054	.041	.176	.163	.100	.029	2
8	.322	.306	.096	.085	.115	.105	.054	.045	.058	.045	.182	.169	.108	.030	2
10	.373	.357	.110	.099	.133	.122	.060	.050	.068	.053	.199	.186	.124	.031	2
12	.425	.407	.125	.112	.151	.139	.067	.056	.077	.061	.259	.246	.141	.034	3
1/4	.492	.473	.144	.130	.175	.162	.075	.064	.087	.070	.281	.268	.161	.036	3
5/16	.615	.594	.178	.162	.218	.203	.084	.072	.106	.085	.350	.337	.193	.169	4
3/8	.740	.716	.212	.195	.261	.244	.094	.081	.124	.100	.389	.376	.233	.210	4

Slotted Pan heads have a flat or gently rounded surface, cylindrical sides and a flat bearing surface. Phillips and Torx (see Torx Pan head) have a more rounded top, cylindrical sides and a flat bearing surface. Commonly used with various combinations in Machine, Self-Tapping, Thread-cutting, Self-Drilling, Thread-Forming and Wood screws.

The Pan head has a general purpose bearing area. It can be substituted in most common applications for Round, Truss or binding heads.